

idle mode.

Detailed Description Text - DETX (186):

At step 746, the UF pump 244 is turned on and water is directed from UF tank 244 through the dialysate circuit 400 back through the pyrogen/ultrafilter 234.

Detailed Description Text - DETX (188):

At step 750, water is rinsed in the tank 202 via sprayer 205. At step 752, water is directed from the tank 202 to dram. At step 754, RO water is sent to the tank 202. At step 756, the blood pump 458 is run in reverse at 75 ml/min. Water is directed through the dialyzer 404 and back to the tank 202 through the chemical ports in the loading platform 250. At step 758, water is drained from the tank 202. At step 760, the pump 212 speed is reduced to 300 ml/min. Water is directed from the tank 202 through the dialyzer 404 and the extracorporeal circuit 400 and then to drain. The system waits until the tank 202 level sensor reads 1 and the flow meter 241 reads less than 300 ml/min.

Detailed Description Text - DETX (190):

After the disinfection mode, the system enters a dialysate preparation sequence 706, described in detail in FIG. 19. At step 717, the process described with step 742 above is performed. At step 719, the RO filters 100 is placed in a produce water mode. The RO alarm monitoring RO conductivity in cell 106 is activated. RO filtered water is then directed to the tank 202. Pump 212 is run at top speed in the forward direction. The tank 202 is placed in a recirculation and deaeration mode, in which water circulates out the tank 202 through degassing line 209, through valves V9 and V20 and back to the tank via valve 232 and line 231 and valve V15. The temperature at thermistor 230 should read a temperature of 30 degrees C. The UF tank 244 is filled with 500 ml of water using the UF pump 242. The tank 202 is filled with reverse osmosis water up in the level at which chemicals are added to the tank 202, and then the RO filter 100 is turned off.

Detailed Description Text - DETX (191):

At step 721, the pressure sensors 500A-C in the extracorporeal circuit are calibrated against pressure sensor 410 in the dialysate circuit. Pressure variations in the dialysate circuit 402 are achieved by moving volumes of fluid between the tank 202 and the ultrafiltration tank 244, with the introduction of fluid into the tank 202 causing an increase in pressure. Similarly, pressure variations in the extracorporeal circuit 400 are achieved by introducing additional volumes of fluid into the extracorporeal circuit via disinfection manifold 494. This calibration test is advantageous in that it permits the use of disposable, off the shelf pressure transducers to be used in the extracorporeal circuit 400. It also permits high accuracy of the monitoring of the blood pressure in the extracorporeal circuit 400 during dialysis. To



US 5702606 A

Patent Number: 5,702,606
Date of Patent: Dec. 30, 1997

REFERENCES

4,097,183	5/1979	Leach	3,544,440
4,138,639	5/1979	Bruckner	3,544,440
4,188,961	9/1979	Dan et al.	3,509,573
4,335,920	9/1980	Corn	3,544,440
4,371,629	10/1980	Leach	3,773,734
4,511,480	5/1982	Recher	3,773,734
4,532,284	6/1982	Corn et al.	3,103,311
4,571,365	7/1983	Johnson	3,951,134
4,598,540	9/1983	Chambers et al.	3,284,873
4,598,020	9/1983	Ward et al.	3,104,101
4,611,768	10/1983	Dickens et al.	3,107,954
4,611,918	11/1983	Kell	3,107,954
4,644,397	6/1984	Corn et al.	3,107,954

Don Data

Feb. 13, 1993, Pat. No.

210,624, 210,625, 210,626

210,627, 210,628, 210,629

210,630, 210,631, 210,632

210,633, 210,634, 210,635

210,636, 210,637, 210,638

210,639, 210,640, 210,641

210,642, 210,643, 210,644

210,645, 210,646, 210,647

210,648, 210,649, 210,650

210,651, 210,652, 210,653

210,654, 210,655, 210,656

210,657, 210,658, 210,659

210,660, 210,661, 210,662

210,663, 210,664, 210,665

210,666, 210,667, 210,668

210,669, 210,670, 210,671

210,672, 210,673, 210,674

210,675, 210,676, 210,677

210,678, 210,679, 210,680

210,681, 210,682, 210,683

210,684, 210,685, 210,686

210,687, 210,688, 210,689

210,690, 210,691, 210,692

210,693, 210,694, 210,695

210,696, 210,697, 210,698

210,699, 210,700, 210,701

210,702, 210,703, 210,704

210,705, 210,706, 210,707

210,708, 210,709, 210,710

210,711, 210,712, 210,713

210,714, 210,715, 210,716

210,717, 210,718, 210,719

210,720, 210,721, 210,722

210,723, 210,724, 210,725

210,726, 210,727, 210,728

210,729, 210,730, 210,731

210,732, 210,733, 210,734

210,735, 210,736, 210,737

210,738, 210,739, 210,740

210,741, 210,742, 210,743

210,744, 210,745, 210,746

210,747, 210,748, 210,749

210,750, 210,751, 210,752

210,753, 210,754, 210,755

210,756, 210,757, 210,758

210,759, 210,760, 210,761

210,762, 210,763, 210,764

210,765, 210,766, 210,767

210,768, 210,769, 210,770

210,771, 210,772, 210,773

210,774, 210,775, 210,776

210,777, 210,778, 210,779

210,780, 210,781, 210,782

210,783, 210,784, 210,785

210,786, 210,787, 210,788

210,789, 210,790, 210,791

210,792, 210,793, 210,794

210,795, 210,796, 210,797

210,798, 210,799, 210,800

210,801, 210,802, 210,803

210,804, 210,805, 210,806

210,807, 210,808, 210,809

210,810, 210,811, 210,812

210,813, 210,814, 210,815

210,816, 210,817, 210,818

210,819, 210,820, 210,821

210,822, 210,823, 210,824

210,825, 210,826, 210,827

210,828, 210,829, 210,830

210,831, 210,832, 210,833

210,834, 210,835, 210,836

210,837, 210,838, 210,839

210,840, 210,841, 210,842

210,843, 210,844, 210,845

210,846, 210,847, 210,848

210,849, 210,850, 210,851

210,852, 210,853, 210,854

210,855, 210,856, 210,857

210,858, 210,859, 210,860

210,861, 210,862, 210,863

210,864, 210,865, 210,866

210,867, 210,868, 210,869

210,870, 210,871, 210,872

210,873, 210,874, 210,875

210,876, 210,877, 210,878

210,879, 210,880, 210,881

210,882, 210,883, 210,884

210,885, 210,886, 210,887

210,888, 210,889, 210,890

210,891, 210,892, 210,893

210,894, 210,895, 210,896

210,897, 210,898, 210,899

210,900, 210,901, 210,902

210,903, 210,904, 210,905

210,906, 210,907, 210,908

210,909, 210,910, 210,911

210,912, 210,913, 210,914

210,915, 210,916, 210,917

210,918, 210,919, 210,920

210,921, 210,922, 210,923

210,924, 210,925, 210,926

210,927, 210,928, 210,929

210,930, 210,931, 210,932

210,933, 210,934, 210,935

210,936, 210,937, 210,938

210,939, 210,940, 210,941

210,942, 210,943, 210,944

210,945, 210,946, 210,947

210,948, 210,949, 210,950

210,951, 210,952, 210,953

210,954, 210,955, 210,956

210,957, 210,958, 210,959

210,960, 210,961, 210,962

210,963, 210,964, 210,965

210,966, 210,967, 210,968

210,969, 210,970, 210,971

210,972, 210,973, 210,974

210,975, 210,976, 210,977

210,978, 210,979, 210,980

210,981, 210,982, 210,983

210,984, 210,985, 210,986

210,987, 210,988, 210,989

210,990, 210,991, 210,992

210,993, 210,994, 210,995

210,996, 210,997, 210,998

210,999, 210,1000, 210,1001

210,1002, 210,1003, 210,1004

210,1005, 210,1006, 210,1007

210,1008, 210,1009, 210,1010

210,1011, 210,1012, 210,1013

210,1014, 210,1015, 210,1016

210,1017, 210,1018, 210,1019

210,1020, 210,1021, 210,1022

210,1023, 210,1024, 210,1025

210,1026, 210,1027, 210,1028

210,1029, 210,1030, 210,1031

210,1032, 210,1033, 210,1034

210,1035, 210,1036, 210,1037

210,1038, 210,1039, 210,1040

210,1041, 210,1042, 210,1043

210,1044, 210,1045, 210,1046

210,1047, 210,1048, 210,1049

210,1050, 210,1051, 210,1052

210,1053, 210,1054, 210,1055

210,1056, 210,1057, 210,1058

210,1059, 210,1060, 210,1061

210,1062, 210,1063, 210,1064

210,1065, 210,1066, 210,1067

210,1068, 210,1069, 210,1070

210,1071, 210,1072, 210,1073

210,1074, 210,1075, 210,1076

210,1077, 210,1078, 210,1079

210,1080, 210,1081, 210,1082

210,1083, 210,1084, 210,1085

210,1086, 210,1087, 210,1088

210,1089, 210,1090, 210,1091

210,1092, 210,1093, 210,1094

210,1095, 210,1096, 210,1097

210,1098, 210,1099, 210,1100

559 by virtue of threaded engagement of flange 561 of female luer 559 with threads 560 of male luer 550 and rotational movement of locking hub 556 relative to female luer 559. In FIG. 37D, an alternative construction is shown in which the locking hub 556 is a separate spinning hub piece that snaps over a circumferential ridge 555. Air vents out of the hub 556 by virtue of the clearance 553 between the locking hub and the integral tube 557.

Detailed Description Text - DETX (144):

The pressure sensors 500A, 500B monitor the pressure in the arterial line 432. If for some reason the arterial fistula needle gets accidentally positioned against the wall of the patient's blood vessel, the pressure will generally drop. The CPU 616 (FIG. 16) monitors the readings of sensors 500A, 500B and, if the pressure drops, it prompts the patient to move about to free up the needle or adjusts the blood pump 458 to bring the pressure to acceptable limits.

Detailed Description Text - DETX (145):

The efficiency of a dialyzer in removing toxins is maximized if the dialysis time is made as short as possible. The faster clearance of urea requires a faster flow rate of the patient's blood. We achieve a faster flow rate by taking advantage of a lower limit of pressure to be monitored by pressure sensor 500B that is safe for conducting dialysis. This pressure limit would be set by the patient's physician. As long as the pressure is above this limit, the pump rate of the blood pump 458 is gradually increased. If the pressure drops below the limit, the blood pump is slowed or stopped if the pressure fails to rebound. When the pressure rebounds, the pump is speeded up. This feedback control of a blood pump 458 by pressure monitors in the arterial line will permit the system to generally shorten the dialysis time, to inform the patient of the expected time for dialysis, and to update the time based on any significant slowing or speeding of the blood pump 458. During this process, the backup pressure sensor 500A provides data in case of a malfunction in sensor 500B. Ordinarily, the pressure sensors 500A and 500B have the same readings. The pressure sensors 500A-C are calibrated against the reference sensor 410 in the dialysate circuit 402 as described below in conjunction with the pressure test of the extracorporeal circuit.

Detailed Description Text - DETX (146):

The blood sensors 446 and 486 are of the same basic design as the blood leak detector, but without the beam splitter and reference photodetector. The sensors 446 and 486 serve two purposes: (1) to detect blood when blood is rim introduced into the extracorporeal circuit 400, thereby permitting calculation of the time elapsed during dialysis, and (2) permitting automatic rinse back control by automatically ending the rinsing back of the blood when the light transmission levels detected by the sensors 486 and 446 rises to a threshold value. As dialysate (or saline) is pumped through the dialyzer 404 during

tent (19)

(4) Patent Number: 5,702,606

(43) Date of Patent: Dec. 30, 1997

DIALYZER

4,097,113	5/19/79	Lundquist	336,948
4,116,638	5/19/79	Harlowe	336,949
4,148,941	9/19/78	Dan et al.	330,573
4,320,820	9/19/80	Gore	334,442
4,321,620	10/19/80	Lundquist	73,704
4,314,480	5/19/82	Bucher	73,704
4,332,364	9/19/82	Gore et al.	210,221,69
4,371,365	3/19/81	Jensen	967,196
4,398,341	8/19/83	Czechowski et al.	134,673
4,399,020	8/19/83	Hendricks et al.	210,961
4,411,783	12/19/83	Chakras et al.	210,964
4,411,816	1/19/84	Kell	210,960
4,444,387	9/19/84	Gore et al.	210,960

Doc Data

Feb. 13, 1995, Pat. No.

210 410A BOLD 61/92

644; 210/643; 210/799

210/643, 645

210/929, 793, 799

(List continued on next page.)

FOREIGN PATENT DOCUMENTS

0930346 9/1993 European Pat. Off.

3442744 6/1996 Germany

831602 1/1987 United Kingdom

OTHER PUBLICATIONS

Cochran et al., *Programmable Machine for Dialysis Rate, Mod. & Biol. Eng. & Comput.*, Nov. 1983, pp. 745-771.

Primary Examiner—John Kim
 Attorney Agent or Firm—McDonald Borthwick Thibault & Berglund

ABSTRACT

A method is described for priming a dialyzer placed in an extracorporeal circuit of a hemodialysis machine to run. The method comprises the steps of substantially filling the extracorporeal circuit and the blood side of the dialyzer with fluid (such as dialysate, H₂O, saline, etc.) and inducing pressure pulses in the fluid. The pressure pulses cause air bubbles from the blood side of the dialyzer to be sheared off the dialyzer membrane. The air bubbles are then condensed from the dialyzer and removed from the extracorporeal circuit. Backflowing of fluid across the dialyzer from the dialysate circuit into the extracorporeal circuit is performed in synchrony with the pressure pulses so as to be the shearing off of air bubbles from the blood side of the dialyzer membrane.

4 Claims, 44 Drawing Sheets

